

Sign & Panel Support Systems

Edge Grip Panel Supports & Projecting Clamp Supports



Ideal for mounting identification and directional signage, wall plaques and displays. The edge grips and projecting supports don't require drilling holes into substrates. They allow the panel to be gripped from sides or top and bottom. Exclusive use of brass, anodized to a satin finish make it great-looking, timeless, and aesthetically effective. Edge grip supports are available for panels up to 10mm (3/8") thick...

ALUMINUM EDGE-GRIP PANEL SUPPORT (SHORT)

- Require no. 8 screw for mounting.
- Spacing from wall: 12.5mm (1/2")
- Panel Thickness: 4-6.5mm (5/32"-1/4")
- Includes Non-Threaded Coupling Anchor

WGS20-7 AL/S	3/4" Dia x 1" L	Anodized Aluminum



WGS20-7 AL/S

ALUMINUM EDGE-GRIP PANEL SUPPORT w/CONICAL BASE (SHORT)

- Require no. 8 screw for mounting.
- Spacing from wall: 20mm (3/4")
- Panel Thickness: 4-6.5mm (5/32"-1/4")
- Includes Non-Threaded Coupling Anchor (Conical Base Support)

WGS20-7 AL/C/S	3/4" Dia x 1-5/32" L	Anodized Aluminum



WGS20-7 AL/C/S

ALUMINUM EDGE-GRIP PANEL SUPPORT

- Require no. 8 screw for mounting.
- Spacing from wall: 20mm (3/4")
- Panel Thickness: 4-6.5mm (5/32"-1/4")
- Includes Non-Threaded Coupling Anchor

WGS20-7 AL	3/4" Dia x 1-5/16" L	Anodized Aluminum



WGS20-7 AL

ALUMINUM EDGE-GRIP PANEL SUPPORT w/CONICAL BASE

- Require no. 8 screw for mounting.
- Spacing from wall: 25mm (1")
- Panel Thickness: 4-6.5mm (5/32"-1/4")
- Includes Non-Threaded Coupling Anchor (Conical Base Support)

WGS20-7 AL/C	3/4" Dia x 1-7/16" L	Anodized Aluminum



WGS20-7 AL/C

ALUMINUM EDGE-GRIP PANEL SUPPORT

- Require no. 8 screw for mounting.
- Spacing from wall: 25mm (1")
- Panel Thickness: 6-8.5mm (5/32"-5/16")
- Includes Non-Threaded Coupling Anchor

WGS25-7 AL	1" Dia x 1-9/16" L	Anodized Aluminum



WGS25-7 AL

ALUMINUM EDGE-GRIP PANEL SUPPORT

- Require no. 8 screw for mounting.
- Spacing from wall: 25mm (1")
- Panel Thickness: 10-12.5mm (3/8"-1/2")
- Includes Non-Threaded Coupling Anchor

WGS25-10 AL	1" Dia x 1-9/16" L	Anodized Aluminum



WGS25-10 AL

ALUMINUM PANEL SUPPORT

- Require no. 8 screw for mounting.
- Spacing from wall: 10mm (3/8")
- Panel Thickness: 4-6.5mm (5/32"-1/4") & 8.5mm (5/16")
- For 8.5mm (5/16") thick panels use WSP20-1 AL/W support

WSP20-1 AL	3/4" Dia x 1" L	Anodized Aluminum
WSP20-1 AL/W	3/4" Dia x 1" L	Anodized Aluminum



WSP20-1 AL

ALUMINUM PANEL SUPPORT

- Require no. 8 screw for mounting.
- Spacing from wall: 20mm (3/4")
- Panel Thickness: 4-6.5mm (5/32"-1/4")
- Includes Non-Threaded Coupling Anchor

WSP20-1-3/8 AL	3/4" Dia x 1-3/8" L	Anodized Aluminum



WSP20-1-3/8 AL

ALUMINUM PANEL SUPPORT

- Require no. 8 screw for mounting.
- Spacing from wall: 30mm (1-3/16")
- Panel Thickness: 4-6.5mm (5/32"-1/4")
- Includes Non-Threaded Coupling Anchor

WSP20-1-3/4 AL	3/4" Dia x 1-3/4" L	Anodized Aluminum



WSP20-1-3/4 AL

ALUMINUM PANEL SUPPORT

- Require no. 8 screw for mounting.
- Spacing from wall: 25mm (1")
- Panel Thickness: 4-6.5mm (5/32"-1/4")
- Includes Non-Threaded Coupling Anchor (Conical Base Support)

WSP20-1-3/8 AL/C	3/4" Dia x 1-9/16" L	Anodized Aluminum



WSP20-1-3/8 AL/C

ALUMINUM PANEL SUPPORT

- Require no. 8 screw for mounting.
- Spacing from wall: 35mm (1-3/8")
- Panel Thickness: 4-6.5mm (5/32"-1/4")
- Includes Non-Threaded Coupling Anchor (Conical Base Support)

WSP20-1-3/4 AL/C	3/4" Dia x 2" L	Anodized Aluminum



WSP20-1-3/4 AL/C

PANEL/SCREW CAP SET

- Panel Thickness: 4-6.5mm (5/32"-1/4")
- Available with Flat (...Set1) or Round (...Set2) Screw Caps

WSP20-1 AL/SET1	3/4" Dia x 1" L	Anodized Aluminum
WSP20-1 AL/SET2	3/4" Dia x 1" L	Anodized Aluminum



WSP20-1 AL/SET1